

**Declaration of Performance  
BSEN 13454 CAB-30**

- |                                                                                                                                                                                                                                                 |                                                                                                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Unique identification code of the product-type:                                                                                                                                                                                              | <b>CAB 30</b>                                                                                                                                                                                      |
| 2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:                                                                                     | <b>Calcium sulfate based binder for the manufacture of screeds for internal use in buildings.</b>                                                                                                  |
| 3. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)::                                                                                                | <b>Delivery number: see delivery notice</b>                                                                                                                                                        |
| 4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:                                                                                                              | <b>System 4</b>                                                                                                                                                                                    |
| 5. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):                                                                                                          | <b>Anhydritec Ltd, 221 Europa Boulevard, Warrington WA57TN, Tel :( 01925 428780) Fax: (01925 428788)</b>                                                                                           |
| 6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:                                                                                                                                | <b>According to System 4, the manufacturer carried out the determination of the product-type on the basis of type testing, type calculation, tabulated values, and factory production control.</b> |
| 7. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:                                                                                                       | <b>not applicable</b>                                                                                                                                                                              |
| 8. <b>Declared performance:</b>                                                                                                                                                                                                                 |                                                                                                                                                                                                    |
| Reaction to fire                                                                                                                                                                                                                                | <b>A1</b>                                                                                                                                                                                          |
| Release of corrosive substances                                                                                                                                                                                                                 | <b>pH ≥ 7</b>                                                                                                                                                                                      |
| Mechanical strength                                                                                                                                                                                                                             | <b>CAB 30</b>                                                                                                                                                                                      |
| Life time                                                                                                                                                                                                                                       |                                                                                                                                                                                                    |
| Calcium sulphate content                                                                                                                                                                                                                        | <b>≥ 85 %</b>                                                                                                                                                                                      |
| Mechanical strength                                                                                                                                                                                                                             | <b>≥ 30</b>                                                                                                                                                                                        |
| Shrinkage and swelling                                                                                                                                                                                                                          | <b>≤ 0,2 mm/m</b>                                                                                                                                                                                  |
| Harmonised technical specification                                                                                                                                                                                                              | <b>BSEN 13454:2004</b>                                                                                                                                                                             |
| 9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.<br>This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 5. |                                                                                                                                                                                                    |

Signed for and on behalf of the manufacturer by:

**José Toña Olabe**

Issued: 01/01/2021

**ANHYDRITEC Ltd.**  
Unit 221, Europa Boulevard,  
Westbrook, Warrington WA5 7TN  
Tel: +44 (0) 1925 428780

