



THE ULTRA-THIN READYMIX FLOWING SUBBASE LEVELLER

Anhydritec® has developed Gyvlon® EXCELIO® technology to offer an unique readymix solution bridging the gap between self-smoothing compounds and bonded screeds.

Gyvlon EXCELIO® is the only readymix liquid flowing screed that can be **bonded at just 12mm**; eliminating the need for site batching multiple mixes, **saving time and money**.

EXCELIO® contributes to preserving the environment thanks to its high recycled content, no plastic packaging and low carbon content.

WHAT DOES EXCELIO® OFFER?

EXCELIO® technology offers building designers a **thin floor construction solution** which provides:

- + Thin section:** Up to **70% reduction** in bonded construction thickness compared with traditional screeds
- + Speed:** Up to **100% faster installation** compared to a thin section smoothing compounds
- + Savings:** Readymix solution, no site mixing, no bag storage, ensuring **high productivity**
- + Versatility:** Suitable for most floor conditions and **all kinds of floor finish**

ALL THE BENEFITS OF GYVLON® PRODUCTS

EXCELIO® technology has **all the benefits** that you have come to expect from Gyvlon screed product based on 30 years' experience:

- **SR1 surface finish achievable**
- **Very high fluidity** for fast installation
- **No shrinkage** greatly reduced cracking, no curling
- **No need for joints** except movement & construction joints
- **No need for a curing membrane**
- **Environmentally friendly, greatly reduced CO₂ and carbon content**

MAIN FEATURES

- ➔ **Quality assured**
Produced in accredited readymix plants
- ➔ **Only 12mm bonded**
Bridging the gap between smoothing compounds and bonded screeds
- ➔ **Green colouration**
To ensure correct product selection



HEALTH AND SAFETY

REMOVES MANUAL HANDLING OF BAGGED MATERIAL, MIXING AND WATER ADDITION



The ultra-thin readymix flowing subbase leveller



The thin and lightweight flowing screed solution



The guaranteed ultra-efficient screed for underfloor heating



The strongest screed for the most demanding situations



The Gyvlon® screed version with faster drying (FD)



Anhydritec's versatile Gyvlon® screed



a product range from



THE ULTRA-THIN READYMIX FLOWING SUBBASE LEVELLER



EXCELIO® is a versatile solution suitable for new construction or renovation.



EXCELIO® makes up for any levelling defects, from 12mm, while allowing up to a 70% reduction in screed thickness.



EXCELIO® is bonded directly after preparation and priming of the substrate. Installation time is reduced by up to 100% thanks to the removals of bag handling and site mixing.



EXCELIO® is a fast and cost-efficient solution due to readymix deliveries and high productivity enabling considerable savings per m².

	Bonded sand cement 40 mm CONCRETE SUBSTRATE	ECO TECHNOLOGY 25 mm CONCRETE SUBSTRATE	EXCELIO TECHNOLOGY 12 mm CONCRETE SUBSTRATE	Smoothing compound 3 mm CONCRETE SUBSTRATE
	THICK SECTION	REDUCED SECTION	OPTIMUM SECTION	THIN SECTION / MULTIPLE LAYER APPLICATION
DESIGN SCOPE	—	★	★★★★★	★
COST EFFICIENCY	★	★★★	★★★★★	★
OVERALL SUITABILITY	—	—	★★★★★	★

OUTSTANDING PERFORMANCE

TECHNICAL CHARACTERISTICS	
Mechanical strength	C30 F8 - BSEN 13813
Dry density	2 050kg/m ³ (± 200)
Design thickness	Bonded 12 - 40 mm (0-4mm sand)
Substrate type	New/existing concrete slab or screed
Substrate preparation	Mechanical preparation
Surface finish	Low skin
Surface regularity	SR1-BSEN 8204-7
Priming requirement (>75% RH)	Liquid DPM (PU/Epoxy) with sand scatter or secondary priming*
Priming requirement (<75% RH)	Multiple coat acrylic primer (typical 1:3/1:1) or water dispersible Epoxy/PU primer*

*Always comply with manufacturers guidance and seek advise

INSTALLATION BENEFITS	
Flow	300mm (±10mm)
Working Time	3 hours from commencement of batching to finish dapping
Joints	None apart from construction/movement joints which need to be mirrored through the floor.
Productivity	Up to 200m ² / hour or 2000m ² / day

Gyvlon® EXCELIO® is a technology of Anhydritec

Non-contractual document. Unauthorized reproduction prohibited - Anhydritec - 05/2021




Our anhydrite binder is composed at **98%** of recycled materials



www.gyvlon.co.uk  www.anhydritec.com

ANHYDRITEC LTD - Unit 221, Europa Boulevard, Westbrook, Warrington, WA5 7TN - T. 01925 428 780 - enquiries@anhydritec.com